
# Single Doors 296 305

SINGLE POINT LOCKING



BS EN 1125

## 296 Reversible Panic Latch



The Exidor 296 is designed for single and double door applications. The unit is operated by a downward thrust of the cross bar to give a speedy exit in panic situations. An adapter for use with a rim cylinder for outside access is supplied as standard.

- Non-handed
- Fire rated for use on timber and steel doors
- Surface mounted
- Adapter supplied for operating with a rim cylinder
- Closed arm design

## 305 Panic Mortice Actuator with Cylinder Mortice Night Latch



The Exidor 305 offers a push bar actuator unit with a cylinder mortice night latch case that can be supplied with or without a Euro profile cylinder for access from the outside. A mortice plate is supplied as standard. The unit provides security on the outside with ease of escape from the inside in panic situations.

- Non-handed
- Surface mounted
- Closed arm design



#### Standard sizes

Standard size panic latches are suitable for single doors up to 1220mm wide. Special sizes are available on request.

#### **Additional options**

The Exidor reversible panic latches can be supplied with:


- Steel door fixings (suffix 'SD' after the product code)
- Microswitch (suffix 'MS' after the product code)

### Optional accessories for the 296 panic latch

- 298 Outside access device knob operated
- 302EA Outside access device with Euro aperture knob operated
- 302EC Outside access device with Euro cylinder knob operated
- 3020A Outside access device with oval aperture knob operated
- 302OC Outside access device with oval cylinder knob operated
- 322EA Outside access device with Euro aperture lever operated
- 322EC Outside access device with Euro cylinder lever operated

## Optional accessories for all the panic latches

- CL1 Mechanical push button outside access device
- CL2 Mechanical push button outside access device with passage facility
- CL3 Quick code mechanical push button outside access device
- CL4 Quick code mechanical push button outside access device with passage facility



296