



## Smoke Alarm – with Hush feature

- Model 29HD-UK



EN14604: 2005

### Technical Specifications

Order Code	29HD-UK
Power Supply	9V Battery (Supplied)
Tamper Proof	Yes
Sensor Technology	Photoelectric Sensing Technology
Hush Feature	Yes – allows nuisance alarms to be temporarily silenced
Temperature Range	0°C to 40°C
Humidity Range	Up to 93% relative humidity (RH) non-condensing
LED's	Red LED's (flashes sequences indicate normal, alarm or hush conditions)
Alarm Sound Output	85 decibels at 3m distance
Alarm Indication	Audible and Visual signals
Push to Test Feature	Yes
Approvals	Certified by VDS to EN14604: 2005 / CE certified
Mounting Options	Ceiling mount (bracket included)
Unit Dimensions	104mm x 104mm x 36mm (in packaging) 100mm x 100mm x 33mm (out of packaging)
Unit Weight	175g (packaged weight) 146g (out of packaging)
Life of Alarm	5-year alarm life
Packaging	Individually packaged in cartons
Case Quantity	6 units
Warranty	5-years

### Key Alarm Features

The Kidde 29HD smoke alarm uses one 9 volt battery. This alarm includes a HUSH control feature that allows nuisance alarms (such as those caused by cooking or steam) to be temporarily silenced.