

# Automatic Extinguisher ABC Dry Powder

### FBA-P1

1 kg (1 m<sup>2</sup> floor space)

### FBA-P2

2 kg (2 m<sup>2</sup> floor space)



Wood, paper, textiles



Flammable Liquids



Flammable Gas



Electrical Risks

Commonly used to protect machinery/plant and where there is a risk of fire such as in boat/vehicle engine compartments.

The unit required is determined by the floor area of that compartment. Only one unit should be installed in any one compartment and should provide the total protection required for that compartment.

- **COMPACT AND ECONOMICAL AUTOMATIC EXTINGUISHER.**
- **5 YEAR WARRANTY.**
- **STORED PRESSURE – EASY LOW-COST MAINTENANCE.**
- **SUITABLE FOR A, B AND C CLASS FIRES.**
- **SAFE FOR USE ON ELECTRICAL EQUIPMENT.**
- **SUPPLIED WITH POWDER COATED, STEEL WIRE BRACKET.**

Model	FBA-P1	FBA-P2
Capacity	1 kg	2 kg
Total Weight	2.14 kg	3.60 kg
Total Height	330 mm	380 mm
Total Width (incl. bracket)	95 mm	125 mm
Working Temp.	-20° to +60°C	
Discharge Time / Temp.	Under 10 secs @ 79°C ± 5°C	
Maximum Area Protected	1 m <sup>2</sup>	2 m <sup>2</sup>
Operating Pressure	12 bar @ 20°C	
Minimum Burst Pressure	55 bar	

### FIXING INSTRUCTIONS

Mount the extinguisher with the discharge head at any angle below the horizontal.

Do not mount the extinguisher with the discharge head pointing upwards.

Do not fit extinguisher close to sources of direct heat such as exhaust manifolds or hot pipes etc.

