

AUTOMATIC FIRE HOSE REEL

Data Sheet



FEATURES:

- Supplied 'Hose On' with a 19mm or 25mm fire hose, 30 metres in length
- Jet/spray fire hose nozzle included
- Certified to EN 671-1
- Includes a wall bracket, inlet pipe, gate valve and hose guide
- 12-bar working pressure
- Operating temperature: -20 and +60°C
- LCPB Approved



www.VigilProducts.com

Unit 11C, Claremont Way, Lakesview Industrial Park, Canterbury CT3 4BF

FIRE HOSE REEL WITH HOSE - MANUAL

The 19mm and 25mm automatic fire hose reels are the ideal solution for tackling Class A fires within your large premises thanks to its ability to continuously supply a steady stream of water. With an automatic fire hose reel, it features an integrated valve which works while you unravel the hose and means water will start to flow through the hose after three full turns of the reel, saving valuable seconds in an emergency. When you've finished, the valve will close as you return the last of the hose to the reel.

Supplied with a 30-metre length of 19mm fire hose and a jet/spray nozzle both pre-installed to the fixed fire hose reel, it comes complete with wall brackets, inlet pipe and hose roller guide. The automatic fire hose reel is often found in factories, warehouses, airports, recycling centres, large public spaces and more.

Part of the Vigil Products range, the 19mm and 25mm fire hose automatic reel has LCPB approval, is certified to EN 671–1 and is constructed of UV–resistant powder–coated steel and brass to increase durability. The fire hose which is on the reel has a tough rubber and PVC construction with a 12–bar working pressure and is compliant with EN 694.

Fixed Hose Reel Contents: Fire Hose Reel, 25mm x 30m Fire Hose, Jet/Spray Fire Hose Nozzle, Wall Brackets, Inlet Pipe, Gate Valve and Hose Roller Guide.











| Product | Fire Hose Reel – 19mm Automatic | Fire Hose Reel – 25mm Automatic |
|------------------|---------------------------------|---------------------------------|
| Product Code | VP-HR19A | VP-HR25A |
| HxWxD | 240x560x570mm | 270x570x570mm |
| Weight | 18.5kg | 21.8kg |
| Material | Powder-coated steel and brass | Powder-coated steel and brass |
| Compliance | Certified to EN 671–1 | Certified to EN 671–1 |
| Working Pressure | 12 Bar | 12 Bar |
| Carton Quantity | 1 | 1 |