# VIGIL®

# CO2 FIRE EXTINGUISHERS

## Data Sheet

**5 YEAR WARRANTY**

VP–XTC2    VP–XTC5

## FEATURES:

- 5–Year Warranty
- BS EN3 approved, UKCA Approved, CE Marked & BSI Kitemarked
- Wall bracket for included for mounting
- Effective against Class B and Electrical fires
- Temperature Range: –20°C to +60°C
- Supplied filled with CO2 (Carbon Dioxide)

# CO2 FIRE EXTINGUISHERS

CO2 Fire Extinguishers, available in 2kg and 5kg sizes, are a dependable and mess–free solution for tackling electrical fires and Class B flammable liquid fires, such as those involving petrol or oils. Designed to protect without causing unnecessary damage, these extinguishers discharge pure carbon dioxide, leaving no residue behind. This makes them a perfect choice for safeguarding sensitive equipment in offices, server rooms, and other professional environments. Lightweight aluminum cylinders ensure they're easy to handle, so anyone can act swiftly in an emergency.

Equipped with frost–free swivel horns for user safety, they deliver a concentrated jet to extinguish fires swiftly and efficiently. Suitable for all premises with live electrical equipment, computers, machinery, small flammable liquid fires, welding, factories, workshops and plant rooms.

| Product | 2kg CO2 Fire Extinguisher | 5kg CO2 Fire Extinguisher |
|---|---|---|
| Product Code | VP–XTC2 | VP–XTC5 |
| H x W x D | 483x263x115mm | 757x289x132mm |
| Fire Rating | 34B | 89B |
| Warranty | 5 Years | 5 Years |
| Capacity | 2kg | 5kg |
| Weight without Horn | 5.82kg | 12.42kg |
| Test Pressure | 250 Bar | 250 Bar |
| Temperature Range | –20°C to +60°C | –20°C to +60°C |
| Operating Pressure | 50 Bar | 50 Bar |
| Approvals | UKCA, CE & BSI Kitemark | UKCA, CE & BSI Kitemark |
| Extinguishing Medium | CO2 | CO2 |
| Carton Quantity | 1 | 1 |
| Carton Weight | 6.74kg | 15kg |
| Carton Dimensions | 510x130x165mm | 780x190x150mm |
| Pallet Quantities | 96 | 44 |

**www.VigilProducts.com**

Unit 11C, Claremont Way, Lakesview Industrial Park, Canterbury CT3 4BF