

Product Data Sheet





Astro U Channel

Intumescent Glazing Channel

- 30 minute rated
- BS 476 Parts 20 & 22 1987
- For use in glass up to 600mm x 600mm
- Intumescent material
- Impervious to water and moisture.
- Easy and clean application.
- Elasticated material grips the glass.





Product Description

U Channel for 6mm glass.

Cost effective, easily installed dry glazing gasket for use in fire doors using clear or wired glass. Elastic composition of the channel grips the glass.

15mm tall 10.5mm wide and supplied in 100 Metre lengths.

Colour - Black Only

Meets appropriate BS and Building Regulation standards.



Product Availability

Sold in 100M coils. Order Code: AFUC6X

Product Code	Product Description	Length
AFUC6X	Astro U Channel	100m

To Order & Specify

Please contact us and quote the following information - Quantity / Product Code / Product Description / Length Typical example:- 5 / AFUC6X / Astro U Channel / 100m

>> Tel: <u>01329 844 500</u> or >> Email: <u>sales@astroflame.com</u>

Installation

Please see installation sheet - This can be requested from our sales team T: <u>01329 844 500</u> or E: <u>sales@astroflame.com</u>

Health and Safety

Please see (SDS) Safety Data sheet - This can be requested from our sales team T: <u>01329 844 500</u> or E: <u>sales@astroflame.com</u>

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME FIRESEALS LTD has no control over the installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product in its intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROflame (Fireseals) Ltd, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice.

T - 01329 844500 F - 01329 844600 Page 2 W - www.astroflame.com E - sales@astroflame.com