

SENTINEL PRO RECESSED

FLEXIBLE EMERGENCY

The Sentinel Pro Recessed is the next generation emergency recessed offering full flexibility thanks to the interchangeable open area and escape route optic design. Delivering a truly flexible self test product to suit all emergency applications.



Features

- Interchangeable open area and escape route options supplied as standard
- Saves time and money - less fittings required
- Non-maintained with Self Test version available
- Advanced LiFePO4 battery technology
- Discreet 50mm emergency head

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
SNP/R	Sentinel Pro Recessed Emergency NM Area & Escape Lens	145	130 lm (Open) 145 lm (Escape)	2W	

Product Information

Warranty	5 Years
Emergency Battery Warranty	5 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	6500K
IP Rating	IP20
Emergency Battery Type	LiFePO4
Voltage	220-240V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Acrylic

Colour Finish	White RAL9003
LED Life Expectancy	36000hours
Power Factor	>0.3
Frequency	50/60Hz
Driver Type	Fixed
Approval	UKCA CE
Electrical Class	Class II
Working Temperature	0°C to +45°C
EM Working Temperature	0°C to +45°C

SENTINEL PRO RECESSED

FLEXIBLE EMERGENCY

Packaging Information

Dimensions (mm)	Ø: 50 x D: 21 mm for lamp head L: 250 x W: 27 x H: 36 mm for Converter
Product Net Weight (kg)	0.182 kg
Barcode	5055807625470
Box Dimensions (mm)	L:170 x W: 160 x D: 60 mm
Box Gross Weight (kg)	0.449 kg

Units/Outer Carton	20
Outer Carton Barcode	15055807625477
Outer Carton Dimensions (mm)	L:360 x W: 340 x D: 325 mm
Outer Carton Gross Weight (kg)	9.6 kg

