

VIGIL 400 AUTOMATIC FIRE NOZZLE

Data Sheet



FEATURES:

- Automatic fire nozzle
- Straight stream, narrow fog and wide fog spray patterns
- Flush function to clean the nozzle
- Flow range: 40 400 litre per minute
- Working pressure of 6 bar
- Throw range: 40 metres
- 2.5" (64mm) BS 336 inlet



www.VigilProducts.com

Unit 11C, Claremont Way, Lakesview Industrial Park, Canterbury CT3 4BF

VIGIL 400 AUTOMATIC FIRE NOZZLE

Automatically adjusting the flow rate to compensate for pressure fluctuations, the Vigil 400 automatic fire nozzle helps to maintain optimum performance. The pressure remains constant no matter which spray pattern you choose, whether that's a straight stream, narrow fog, wide fog or flush output.

Using the twist adjusting ring, it's easy to switch between the different spray settings, and even features raised identification so you can operate the turbo nozzle even in low visibility conditions. With a flow range of between 40 and 400 litres per minute, you'll always have plenty of extinguishing power.

Manufactured for Vigil Products in accordance with BSEN-15182, it comes complete with an integral 2 ½" instantaneous alloy male inlet (BS 336) for UK fixings. With a hard anodised aluminium body and ABS handle with a rubber bumper, the Vigil 400 automatic fire nozzle has a lightweight and robust design that's perfect for demanding environments. The moulded-rubber teeth create different fog patterns.

The automatic fire nozzles are a popular choice by professional firefighters and are regularly used for wash-down applications, heavy dust suppression, and in marine and oil rig environments.









Product	Vigil 400 Automatic Fire Nozzle
Product Code	VP-FNSXA400
HxWxD	150x360x300mm
Weight	1.50kg
Compliance	BS336
Working Pressure	6 Bar
Throw Range	30 metres
Material	Aluminium body, ABS handle and rubber bumper
Carton Quantity	5
Carton Dimensions	330x400x770mm
Carton Weight	8.90kg