

FIREXO 9L ALL FIRES EXTINGUISHER

PRODUCT	FIREXO 9L ALL FIRES
MODEL/PRODUCT NO.	809-765-347-906
CAPACITY	9 LITRES
OVERALL PRODUCT HEIGHT	595 mm
CYLINDER HEIGHT	490 mm
CYLINDER DIAMETER	184 mm
CYLINDER MATERIAL	STEEL
PRESSURISING GAS	NITROGEN
TEST PRESSURE	30 BAR
VORKING PRESSURE	12 BAR
VEIGHT (FULL)	15.13 KG
VEIGHT (EMPTY)	4.6 KG
SPRAY RANGE	1-4 m
DISCHARGE TIME	45-55 seconds
TEMPERATURE RANGE	-15 °C / +60 °C
WARRANTY	5 YEARS
FIRE RATINGS	55A/183B/C/D/ELECTRICAL/75F/LITHIUM-ION











Portable Fire Extinguishers KITEMARK™

METHOD OF USE

In the event of a fire hold extinguisher upright, pull out safety pin, point hose at base of fire, squeeze handle and sweep side to side.

Discharge entire contents onto the fire from a 1m-3m distance.

Store upright and away from direct sunlight or heat source.

Protect from frost.

Replace or recharge after use.

Tested on electrical equipment fires to 35kV.

© FIREXO 2023

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, FIREXO does not accept any responsibility or legal liability for any errors or omissions.

ALL FIRES ONE ANSWER