



Section 1

FIRE FIGHTING EQUIPMENT

FirePower

FLUORINE FREE FOAM EXTINGUISHERS

Stored Pressure

- Suitable for class A B fires
- CE approved nickel plated brass valve
- CE approved internally lined phosphated steel cylinder with polyester powder coating
- 100% leak detected
- Tested to 35kV
- Pressure release valve included
- Production under ISO9001 quality system
- CE, UKCA, BS EN3, BSI Kitemark
- 2L model complete with wire bracket
- 5 year warranty



Model Number	FPPF2
Capacity (L)	2
Cylinder Diameter (mm)	110
Fire Rating	5A/34B
BSI Kitemark	YES
MED Approved	NO
Extinguisher Weight (kg)	4
Range of Throw (m)	>2
Duration of Discharge (secs)	>6
Packing Size (LxWxH) (mm)	125x115x395
Working Pressure (bar) at 20°C	14
Test Pressure (bar)	30
Operation Temperature (°C)	+5 to +60

* Transport Classification: Non-Flammable, Non-Toxic Gas. UN No.1044 Class 2.2



FIRE FIGHTING EQUIPMENT





Section 1

FIRE FIGHTING EQUIPMENT

FirePower

FLUORINE FREE FOAM EXTINGUISHERS

Stored Pressure

- Suitable for class A B fires
- CE approved nickel plated brass valve
- CE approved internally lined phosphated steel cylinder with polyester powder coating
- 100% leak detected
- Tested to 35kV
- Pressure release valve included
- Production under ISO9001 quality system
- CE, UKCA, BS EN3, BSI Kitemark
- 2L model complete with wire bracket
- 5 year warranty



Model Number	FPPF3
Capacity (L)	3
Cylinder Diameter (mm)	130
Fire Rating	13A/70B
BSI Kitemark	YES
MED Approved	NO
Extinguisher Weight (kg)	5.7
Range of Throw (m)	>4
Duration of Discharge (secs)	>9
Packing Size (LxWxH) (mm)	145x140x460
Working Pressure (bar) at 20°C	14
Test Pressure (bar)	30
Operation Temperature (°C)	+5 to +60

* Transport Classification: Non-Flammable, Non-Toxic Gas. UN No.1044 Class 2.2



FIRE FIGHTING EQUIPMENT





Section 1

FIRE FIGHTING EQUIPMENT

FirePower

FLUORINE FREE FOAM EXTINGUISHERS

Stored Pressure

- Suitable for class A B fires
- CE approved nickel plated brass valve
- CE approved internally lined phosphated steel cylinder with polyester powder coating
- 100% leak detected
- Tested to 35kV
- Pressure release valve included
- Production under ISO9001 quality system
- CE, UKCA, BS EN3, BSI Kitemark
- 2L model complete with wire bracket
- 5 year warranty



Model Number	FPPF6
Capacity (L)	6
Cylinder Diameter (mm)	162
Fire Rating	21A/144B
BSI Kitemark	YES
MED Approved	NO
Extinguisher Weight (kg)	10.4
Range of Throw (m)	>4
Duration of Discharge (secs)	>15
Packing Size (LxWxH) (mm)	175x175x570
Working Pressure (bar) at 20°C	14
Test Pressure (bar)	30
Operation Temperature (°C)	+5 to +60

* Transport Classification: Non-Flammable, Non-Toxic Gas. UN No.1044 Class 2.2



FIRE FIGHTING EQUIPMENT





Section 1

FIRE FIGHTING EQUIPMENT

FirePower

FLUORINE FREE FOAM EXTINGUISHERS

Stored Pressure

- Suitable for class A B fires
- CE approved nickel plated brass valve
- CE approved internally lined phosphated steel cylinder with polyester powder coating
- 100% leak detected
- Tested to 35kV
- Pressure release valve included
- Production under ISO9001 quality system
- CE, UKCA, BS EN3, BSI Kitemark
- 2L model complete with wire bracket
- 5 year warranty



Model Number	FPPF9
Capacity (L)	9
Cylinder Diameter (mm)	182
Fire Rating	27A/233B
BSI Kitemark	YES
MED Approved	NO
Extinguisher Weight (kg)	14.8
Range of Throw (m)	>4
Duration of Discharge (secs)	>15
Packing Size (LxWxH) (mm)	192x192x620
Working Pressure (bar) at 20°C	14
Test Pressure (bar)	30
Operation Temperature (°C)	+5 to +60

* Transport Classification: Non-Flammable, Non-Toxic Gas. UN No.1044 Class 2.2



FIRE FIGHTING EQUIPMENT

